

MATERIAL SAFETY DATA SHEET

IDENTITY: FSC-88

Date of Preparation: 2/1/02

SECTION I - Material and Manufacturer Identification

Manufacturer's Name & Address

Coastal Enterprises Company
P.O. Box 4875
Orange, CA 92863-4875

For Information:
(800) 845-0745

Product Name: FSC-88 Quick Dry Primer

DOT Proper Shipping Name: Primer/Filler

ID Number: UN1263, Packing Group II

DOT Hazard Classification: Flammable Liquid, Hazard Class 3, Class 55

Emergency Telephone Numbers:

Transportation Emergencies: Call CHEMTREC
(800) 424-9300 (202) 483-7616 (Collect) from
Alaska & Hawaii

Health Emergencies: Call LOS ANGELES
POISON INFORMATION CENTER (24 hrs.)
(800) 356-3129

SECTION II - Hazardous Ingredients/SARA III Information

Reportable Components	Cas Number	Vapor Pressure Mm Hg @ Temp	Weight Percen
Naphtha (Petroleum), Light Aliphatic ACGIH/TWA: 300 PPM; OSHA PEL/TWA: 300 PPM	64742-89-B	26 100 F	20
VM & P Naphtha ACGIH TLV: 500 PPM	Mixture	15 68 F	17
Magnesium Silicate Hydrate ACGIH/TWA: 2mg/m3; OSHA TWA: 20 MPPCF	14807-96-6	N/A N/A	14
Naphtha (Petroleum), Heavy Alkylate ACGIN TLV/TWA: 300 PPM	64741-65-7	2.6 68 F	8.8
Kaolin ACGIN TLV: 2mg/m3 Respirable; OSHA PEL: 5mg/m3 Respirable, 10mg/m3 TOTAL	1332-58-7	N/A N/A	7
Naphtha (Petroleum), Medium Aliphatic OSHA PEL/TWA: 100 PPM; ACGIN /TWA: 100 PPM	64742-88-7	0.5 68 F	2.2
* Xylene (Mixed Isomers) OAHHA PEL: 100 PPM; ACGIN TLV: 100 PPM; ACGIN STEL: 150 PPM; NIOSH: 100 PPM	1330-20-7	6.72 70 F	2.1
# Crystalline Silica (Quartz) ACGIN TLV: 10mg/m3; OSHA Pel: 10 mg/m3 (Respirable Dust)	14808-60-7	N/A N/A	.11

*Indicates toxic chemical (s) subject to the reporting requirements of Section 313 of Title III and of 40 CFR 372 # Indicated toxic chemical (s) subject to the reporting requirements of Calif. Prop. 65.

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

May cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and even asphyxiation.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Eyes: May cause severe irritation, redness, tearing, and blurred vision. Skin: Redness or dryness.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal.

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE: Irritation of skin, eyes, and respiratory tract. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal. CHRONIC: Prolonged or repeated exposure above TLV may result in permanent brain and nervous system damage. CHRONIC: Prolonged or repeated exposure to this product may cause birth defects or other reproductive harm. CHRONIC: Prolonged or repeated exposure to this product may cause cancer. CHRONIC: Contains crystalline silica that IARC has concluded may cause cancer in animals but limited evidence of cancer in humans. Risk of cancer depends on duration and level of exposure. In coatings products, risk is due primarily to inhalation of sanding dust. Prolonged exposure to respirable crystalline silica (quartz) may cause delayed (chronic) lung injury (silicosis).

CARCINOGENICITY

NTP? No IARC MONOGRAPHS? Yes OSHA REGULATED? Yes

WARNING! This product contains chemical (s) known to the State of California to cause cancer. (California Health and Safety Code Section 25249.5) (Prop. 65) **WARNING!** This product contains chemical (s) known to the State of California to cause birth defects or other reproductive harm. (California Health and Safety Code Section 25249.5) (Prop. 65)

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE

May be aggravating to some skin and respiratory conditions, and to pre-existing liver and/or kidney disorders.

EMERGENCY AND FIRST AID PROCEDURES

EYES: Flush with large amounts of water for at least 15 minutes. Take to a physician. SKIN: Wash affected areas with soap and water. Remove contaminated clothing. If irritation persists, consult a physician. INHALATION: Remove to fresh air. Restore breathing. Treat symptomatically. Consult physician. INGESTION: Drink 1 or 2 glasses of water to dilute. DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. TREAT SYMPTOMATICALLY.

SECTION VII - Precautions For Safe Handling and Use

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Eliminate all ignition sources. Dike, contain, or absorb with inert materials. Transfer to containers for recovery or disposal. Prevent runoff into sewers, streams, or other bodies of water.

WASTE DISPOSAL METHOD

Dispose of in accordance with local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Do not store or use near sources of high temperatures, near fire or open flame, or other ignition sources.

OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. Avoid prolonged or repeated exposure to levels above TLV. KEEP OUT OF REACH OF CHILDREN.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION

If TLV is exceeded, use NIOSH/MSHA approved organic vapor, mist and dust, supplied air, or self-contained breathing apparatus. Avoid breathing sanding dust. **PRODUCT CONTAINS CRYSTALLINE SILICA.** Long-term exposure to Crystalline Silica may cause lung damage and cancer. Risk depends upon duration and level of exposure to sanding dust. When sanding, use NIOSH/MSHA approved dust mask.

VENTILATION

Use adequate mechanical (general and/or local) ventilation to maintain exposure below TLV.

PROTECTIVE GLOVES

Wear resistant gloves such as Nitrile Rubber.

EYE PROTECTION

Use chemical splash goggles or OSHA permitted safety glasses.

OTHER PROTECTIVE EQUIPMENT

Wear impervious clothing, eye wash station.

HYGIENIC PRACTICES

Wash hands before eating or using restrooms. Remove and wash all contaminated clothing before reuse.

The information contained herein is based on data believed by Coastal Enterprises Company to be accurate, but we do not assume any liability for the accuracy of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. Anyone intending to rely on any recommendation or to use any equipment, technique or material mentioned should also satisfy himself that he can meet all applicable safety and health standards. Determination of the suitability of any information or product for the use contemplated by any user, the manner of that use, and whether there is any infringement of patents, is the sole responsibility of the user.
